


LAMP PHOTOMETRIC REPORT

MODEL: 92EL05630/WHBK		
POWER: 5W	VOLTAGE: 230V	WORKING VOLTAGE: 230V
MANUFACTURER: Elmark Industries JSC		

TOTAL FLUX: 378.21 lm



γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%
10	725.2	752.3	764.0	698.7	636.4	674.1	752.1	755.9	0- 10	82.59	82.59	21.8
20	332.5	344.4	348.8	327.6	309.5	326.3	357.5	356.3	10- 20	139.9	222.5	58.8
30	138.7	134.3	127.9	130.4	133.8	146.6	153.0	147.4	20- 30	102.7	325.2	86
40	23.13	19.70	17.74	19.12	21.32	26.24	29.46	27.09	30- 40	42.82	368.0	97.3
50	4.697	4.433	4.032	4.144	4.403	4.482	4.554	4.427	40- 50	7.585	375.6	99.3
60	1.139	1.072	1.078	0.9214	0.9401	1.271	1.499	1.291	50- 60	2.327	377.9	99.9
70	0.0299	0.0109	0	0.0041	0	0.0000	0.0136	0.0027	60- 70	0.2732	378.2	100
80	0	0	0	0	0	0	0	0	70- 80	0.0017	378.2	100
90	0	0	0	0	0	0	0	0	80- 90	0	378.2	100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
C Interval: 10.0DEG
Test Speed: MEDIUM
Temperature:25.3°C
Operators:
Test Date:08 December 2022

γ Range: 0 - 90DEG
 γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

γ Range: 0 - 90DEG
γ Interval: 2.5DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.00.456
Humidity:65.0%
Test Distance:6.265m [K=1.0000]
Remarks:

```

